

A super tough coating containing pure stainless steel pigment in an ultra durable resin system. Seals, beautifies and protects metal, wood, ceramics and more. Helps prevent deterioration caused by harsh chemicals, severe atmospheres or conditions.

Tack Free in 5 Minutes - Hard Cure in 2 hours

FOR USE ON: Radiators, Steam Pipes, Fire Hydrants, Exhausts, Mufflers, Parking Meters Chain and Wire Fences, Boilers, Engines, Grills, Lockers, Heat Exchangers Ovens Storage and Mixing Tanks, Chemical Processing and Production Equipment, Vehicle Maintenance, HVAC Trades, Marine Agricultural and Military Equipment, Road Equipment, Oil Drilling Equipment, Aircraft Maintenance, Restaurant Equipment

DIRECTIONS:

1. Surface must be clean and dry before painting. For best results, use when can is between 70° and 90°F (21° and 32°C).
2. Shake can at least one minute before and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25 cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn spray button 1/4 turn or remove and clean button slot. Do not stick objects into can opening.
5. After painting, turn can upside down and spray for 2 seconds to clean spray button.
6. Discard empty can in trash pick up. Do not incinerate or compact.

CAUTION: Acetone 67-64-1, Toluol 108-88-3, Propane 74-98-6, N-Butane 106-97-8, Xylene 1330-20-7, Ethyl Benzene 100-41-4, Mineral Spirits 64742-47-8. OTHER INGREDIENTS: "Contents Partially Unknown".

DANGER: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C). **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. **NOTICE:** Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain damage and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources or ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin, and clothing.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING: Health, 1; Flammability, 4; Reactivity, 3; Personal Protection, B. For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN

DISTRIBUTED BY:

MKG SALES ASSOCIATES, INC.

Medford Industrial Park

130 Miller Road, Medford, NJ 08055

Phone: (800) 945-0555 • Fax: (609) 953-4701

www.mkg-sales.com

Made in USA



STEEL KOTE

Stainless Steel Coating

Contains 100% Pure 316L Stainless Steel Pigment

Heat Resistant To 400°F

Provides Superior Rust Protection

Satin Sheen Finish

PRODUCT # 7074000

DANGER:

EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.

CONTENTS UNDER PRESSURE.

SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 13 OZ.

(368 Grams)