# SAFETY DATA SHEET

### 1. Identification

Product number 1015600

Product identifier 19 OZ LOOK OUT LB 24PK (2-12)

Revision date 11-18-2015

Company information MKG SALES & ASSOCIATES

130 MILLER ROAD

MEDFORD, NJ 08055 United States General Assistance 609-953-4700

Company phoneGeneral AssistanEmergency telephone US1-866-836-8855Emergency telephone outside1-952-852-4646

JS

Version # Supersedes 04

date Recommended 08-11-2015
use cleaner
Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSpecific target organ toxicity, single exposureCategory 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. May cause damage to organs.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this

product.

**Response** If exposed or concerned: Call a poison center/doctor.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Methanol		67-56-1	2.5 - 10
Ethyl Alcohol		64-17-5	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below	reportable levels		90 - 100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product name: 19 OZ LOOK OUT LB 24PK (2-12)

SDS US

### 4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Most important

Rinse mouth. Get medical attention if symptoms occur.

symptoms/effects, acute and

Direct contact with eyes may cause temporary irritation.

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** 

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Not available.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards

Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

### 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Methanol (CAS 67-56-1)	PEL	260 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
<b>US. ACGIH Threshold Limit Values</b>			
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
Methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Methanol (CAS 67-56-1)	STEL	325 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

#### **Biological limit values**

**ACGIH Biological Exposure Indices** 

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 ma/l	Methanol	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

controls

Appropriate engineering

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

upplier.

Other Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Physical state Gas. **Form** Aerosol. Not available. Color Odor Not available. **Odor threshold** Not available. Not available. Ha Not available. Melting point/freezing point

Initial boiling point and boiling

range

212 °F (100 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

**Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

**Explosive properties** Not explosive. Oxidizing properties Not oxidizing. Specific gravity 0.916 estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** May cause damage to organs by inhalation.

**Skin contact**No adverse effects due to skin contact are expected. **Eye contact**Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

### **Acute toxicity**

Product	Species	Test Results
19 OZ LOOK OUT LB 24PK	(2-12)	
<u>Acute</u>		
Dermal		
LD50	Rat	22114 mg/kg
Inhalation		
LC50	Rat	204 mg/l/4h
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
2000	Wouse	
	Dot	52 %, 120 Minutes
F:1   A        (0.4.0.04.47.5)	Rat	1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		
<u>Acute</u> Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral		31.3 mg/i, 0 Hours
LD50	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
Methanol (CAS 67-56-1)	· · ·	10 110 mg/kg
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		82.1 mg/l, 6 Hours
Oral		<b>3</b> / 5 - 5 - 5
LD50	Pig	> 5000 mg/kg
	Rat	1187 - 2769 mg/kg

Product name: 19 OZ LOOK OUT LB 24PK (2-12)

SDS US

Components Species Test Results

Propane (CAS 74-98-6)

<u>Acute</u>

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

**Test Results** 

> 10000 mg/l, 48 hours

Rat 1355 mg/l

658 mg/l/4h

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

**Species** 

Specific target organ toxicity -

single exposure

May cause damage to organs. Eyes. Skin. Central nervous system. Respiratory system.

Gastrointestinal tract.

Specific target organ toxicity -

repeated exposure

**Product** 

Not available.

Aspiration hazard Not likely, due to the form of the product.

### 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

19 OZ LOOK OUT LB	24PK (2-12)		
Aquatic			
Algae	IC50	Algae	5714 mg/L, 72 Hours
Fish	LC50	Fish	57589 mg/L, 96 Hours
Components		Species	Test Results
Ethyl Alcohol (CAS 64	l-17-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales prom	nelas) > 100.1 mg/l, 96 hours
Methanol (CAS 67-56	-1)		
Aquatic			

Water flea (Daphnia magna)

Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

EC50

LC50

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Crustacea

Fish

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

 Butane
 2.89

 Ethyl Alcohol
 -0.31

 Methanol
 -0.77

 Propane
 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

## 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA** 

UN number UN1950

**UN proper shipping name** Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

**IMDG** 

UN number UN1950
UN proper shipping name AEROSOLS

### Transport hazard class(es)

**Class** 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

LTD QTY Not applicable.

DOT



IATA; IMDG



### 15. Regulatory information

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methanol (CAS 67-56-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

Product name: 19 OZ LOOK OUT LB 24PK (2-12)

SDS US

Product #: 1000005676 Version #: 04 Revision date: 11-18-2015 Issue date: 09-24-2014

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Methanol	67-56-1	2.5 - 10	

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

### **US** state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8) Methanol (CAS 67-56-1)

### **US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

# US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

### US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Butane (CAS 106-97-8) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

#### **US.** California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1) Listed: January 1, 1988

### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or region Inventory name On inventory (yes/no)\*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

 Issue date
 09-24-2014

 Revision date
 11-18-2015

Version # 04

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.