6062610

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.					
PRODUCT NUMBER: 6062610 IDENTITY: GREEN DEATH	+ 20A		Revision Da	te: 01/23/2003	
Section I					
Manufacturer's Name:MKG SALES ASSOCIATES, INC.*** Address: MEDFORD INDUSTRIAL PARK 130 MILLER RD MEDFORD State: NJ Zip Code:08055			Emerge 800/25 Inform	Telephone Numbers: Emergency: 800/255-3924 Information: 609/953-4700	
HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)					
Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM %	
AROMATIC PET. DISTILLATES ISOPROPYL ALCOHOL PROPANE/N-BUTANE	64742-94-5 67-63-0 68476-86-8	400 PPM		N/A N/A	

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

______ Boiling Point: 350F+ Specific Gravity (water=1) 0.89

Melting Point: Vapor Pressure(mm Hg) <5 N/A Vapor Density(AIR=1) Solubility in Water: 4 Evaporation Rate: <1 0%

(Butyl Acetate=1) Appearance and Odor: BROWN COLORED SPRAY, PETROLEUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

UEL: 6.0

Flash Point(Method Used):142F TCC Flammable Limits: LEL:1.0

Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS

6062610

Section V: REACTIVITY DATA PRODUCT NUMBER: 452

Stability: Unstable: Conditions to avoid: Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES

Incompatability (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY

PRODUCE CARBON MONOXIDE.

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS. INGESTION: NAUSEA. SKIN: IRRITATION AND REDDENING. EYES: IRRITATION AND REDDENING.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF INDICATED. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. EYES: FLUSH WITH WATER FOR 15 MINUTES AND CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE EMPTY CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Other Precautions: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS.

Ventilation: Local Exhaust:ADEQUATE

Mechanical: N/A Special: N/A

N/A

Protective Gloves:RECOMMENDED

Eye Protection: SAFTEY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USE.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices: WASH HANDS AFTER USE.

6062610